



TeamDrive Host-Server Reference Guide

Release 3.0.013.5

Eckhard Pruehs

November 10, 2014

CONTENTS

1	Copyright Notice	1
2	Trademark Notice	3
3	Introduction	5
4	Hosting Service API	7
4.1	API Basics	7
4.2	Example API Call	7
4.3	API Usage Recommendations	8
4.4	Error Handling	8
4.5	Requirements	10
4.6	Retrieve Depot Information	10
4.7	Retrieve Space Information	11
4.8	Delete Depot	12
4.9	Deactivate Depot (added in 3.0.002)	13
4.10	Delete a Space	14
4.11	Set Depot Limits (added in 3.0.003)	14
4.12	Increase Depot Limits	15
4.13	Decrease Depot Limits	16
4.14	Authorize Users to Create Spaces in other Depots	17
4.15	Remove Authorization from Users to Create Spaces in Other depots	18
4.16	Update Contract (added in 3.0.002)	19
4.17	Create and Deploy a Depot	19
4.18	Create Depot Without User (added in 3.0.002)	21
4.19	Assign User to Depot (added in 3.0.002)	22
4.20	Get Depot Document	22
5	API Error Codes	25
6	Appendix	27
6.1	Abbreviations	27

COPYRIGHT NOTICE

Copyright © 2014, TeamDrive Systems GmbH. All rights reserved.

TeamDrive Systems GmbH

<https://www.teamdrive.com>

Max-Brauer-Allee 50

22765 Hamburg, Germany

Email: info@teamdrive.com

TRADEMARK NOTICE

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

Apache HTTP Server, Apache, and the Apache feather logo are trademarks of The Apache Software Foundation.

MySQL is a registered trademark of Oracle and/or its affiliates.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices.

VMware is a trademark or registered trademark of VMware, Inc. in the United States and/or other jurisdictions.

“Amazon Web Services”, “Amazon S3” are trademarks of Amazon.com, Inc. or its affiliates in the United States and/or other countries.

“Red Hat Linux” and “CentOS” are trademarks of Red Hat, Inc. in the U.S. and other countries.

All other names and trademarks used herein are the property of their respective owners.

INTRODUCTION

This Reference Guide describes some of the TeamDrive Host Server internals, e.g. a description of the XML-RPC-based Host Server API and possible API Error Codes.

HOSTING SERVICE API

4.1 API Basics

The TeamDrive Enterprise Server architecture provides an extensive application programming interface (API) that can be used to:

- Script/automate processes that would otherwise require use of the web-based administration console
- Obtain information about various entities and parameters (e.g. user names, licenses, storage).

The API is based on XML Remote Procedure Calls (see <http://en.wikipedia.org/wiki/XML-RPC> for a detailed description). Only HTTP POST-Requests will be accepted. Each request must include a checksum in the URL appended as a parameter. This checksum is created by calculating a MD5 checksum over the request body appended with a server-specific salt value. The checksum value must be provided in lower case characters, e.g. by passing it through the `tolower()` function of the respective programming language.

On the TeamDrive Registration Server Administration Console, this salt value can be obtained from the `APIChecksumSalt` system setting (“*Edit Settings* -> *RegServer*”). On a TeamDrive Hosting Service, this value is stored in the configuration setting `APISalt` and must match the value of the Registration Server this Hosting Service has been associated with.

Each request also needs to include a `<requesttime>` which is the current timestamp converted to integer.

The URL to access the TeamDrive Hosting Service API looks as follows:

```
https://<domain>/pbas/pl_as/api/api.htm?checksum=<md5>
```

Please replace `<domain>` with the host name of the Host or Registration Server you want to connect to. `<md5>` needs to be replaced with the checksum of the current API request.

If you are accessing the API over a local network or a VPN, you can use plain HTTP. However, when sending the data over an insecure network, you must use HTTPS for security reasons.

Note: API access is verified by the IP address the request originated from. On the Registration Server, check the setting `API_IP_ACCESS` (“*Edit Distributor Settings*” -> “*API*” -> “*API_IP_ACCESS*” via the Administration Console) and make sure that the external IP address of the system performing the API call is included in the list.

On the Hosting Service, the IP address must be added to the configuration setting `APIAccessList`.

4.2 Example API Call

The following shell script example outlines how an API call is generated and how the required MD5 checksum is calculated. In this example `curl` is used to perform the actual API call. The result is printed to the console:

```
#!/bin/sh

URL="http://hostserver.local/pbas/pl_as/api/api.htm"
CHECKSUM="d3b07384d113edec49eaa6238ad5ff00"
```

```
TIMESTAMP=`date "+%s"`
REQUEST="<?xml version='1.0' encoding='UTF-8' ?>\
<teamdrive><apiversion>3.0.003</apiversion>\
<command>getdepotdata</command>\
<requesttime>${TIMESTAMP}</requesttime>\
<username>YourUserName</username>\
</teamdrive>"
MD5=`echo -n "$REQUEST$CHECKSUM" | md5sum | cut -f1 -d" "`
curl -d "$REQUEST" "$URL?checksum=$MD5"
```

4.3 API Usage Recommendations

On your side of the (web-) application, you must ensure that only successfully logged in users can view or change their own data. Users should never be allowed to view data from other TeamDrive Users. Only users associated with your distributor code can be managed with API calls coming from your IP. For users with a foreign distributor code you will receive a URL which must be displayed to the user so that they can login to the website of their distributor.

4.4 Error Handling

The following errors can occur due to misconfiguration or service failures, they may not return valid XML. Your application should handle these failures appropriately.

4.4.1 Wrong Apache configuration

Request:

```
http://<domain>/pbas/p1_as/api/service.html
```

Answer:

```
<html><head>
<title>404 Not Found</title>
</head><body>
<h1>Not Found</h1>
<p>The requested URL /pbas/p1_as/api/service.html was not found on this server.</p>
<hr>
<address>Apache/2.2.9 (Fedora) Server Port 80</address>
</body></html>
```

4.4.2 Apache handler could not be addressed

Request:

```
http://<domain>/pbas/p1_as/api/service.html
```

Answer:

```
<head><TITLE>503 Service Unavailable</TITLE></head><body><H1>503 Service
Unavailable</H1><P><H3>Error Processing Request</H3></body> The following
error occurred in \'SendCGIRequest("td2api")\' while processing
your request: -12996 (-12946).
```

4.4.3 Application errors

Application errors will return error messages in an XML format like this:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode></primarycode>
    <secondarycode></secondarycode>
    <message></message>
  </exception>
</teamdrive>
```

<primarycode> and <secondarycode> (optional) are integer values. <message> is a text.

Error codes regarding the API will start at -30100 (see *API Error Codes* (page 25)).

General errors with the PrimeBase Virtual Machine or database connection are in the range between 0 and -23000.

4.4.4 Programming errors

If a program error occurs, the server will return an error similar to the following one:

```
<HTML><HEAD><TITLE>Execution Error</TITLE></HEAD><BODY>
<H2>Execution Error</H2><FONT SIZE = +1>An error occurred while processing
your request: <BR>Primary error code: <B>-10005</B>, Secondary error code:
<B>0</B><BR><FONT SIZE = 0><H3>"api_init.sys"@client line 7: ';' token
expected in place of 'execute'.</H3></BODY></HTML>
```

4.4.5 Invalid Requests

Invalid requests will return one of the following errors:

Unknown IP Address

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <exception>
    <primarycode>-30000</primarycode>
    <secondarycode></secondarycode>
    <message>Access denied</message>
  </exception>
</teamdrive>
```

Invalid Command

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <exception>
    <primarycode>-30001</primarycode>
    <secondarycode></secondarycode>
    <message>Invalid Command</message>
```

```
    </exception>
</teamdrive>
```

Invalid Request

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <exception>
    <primarycode>-30002</primarycode>
    <secondarycode></secondarycode>
    <message>Invalid Request</message>
  </exception>
</teamdrive>
```

Invalid XML

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <exception>
    <primarycode>-30003</primarycode>
    <secondarycode></secondarycode>
    <message>Invalid XML</message>
  </exception>
</teamdrive>
```

4.5 Requirements

A TeamDrive user can have different Depots on different Hosting Services. A record of which user has which depot can be stored on the Registration Server using “setdepotforuser” or in your own system by storing the username, the Hosting Service URL and the depot id.

4.6 Retrieve Depot Information

Note: This request must be sent to each Hosting Service where the user has a Depot.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>getdepotdata</command>
  <requesttime></requesttime>
  <username></username>
</teamdrive>
```

Reply:

Note: Storage and transfer quantities are in Bytes: 1 KB = 1024 Bytes. <userlist> is a list of Usernames which can access the depot to create spaces. This list is empty for a default depot.

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <depotdata>
    <depot>
      <depotid></depotid>
      <name></name>
      <status></status>
      <accountnumber></accountnumber>
      <created></created>
      <storagelimit></storagelimit>
      <storageused></storageused>
      <transferlimit></transferlimit>
      <transferused></transferused>
      <userlist></userlist>
    </depot>
    <depot>...</depot>
    <depot>...</depot>
  </depotdata>
</teamdrive>
```

4.6.1 Error Cases

No Depot on the Server for the User

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30301</primarycode>
    <secondarycode></secondarycode>
    <message>No Depot for User</message>
  </exception>
</teamdrive>
```

4.7 Retrieve Space Information

Note: This request must be sent to each Hosting Service where the user has a Depot.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>getspacedata</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
</teamdrive>
```

Reply:

Note: Storage and transfer quantities are in Bytes: 1 KB = 1024 Bytes.

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <spacedata>
    <space>
      <spaceid></spaceid>
      <name></name>
      <created></created>
      <owner></owner>
      <status></status>
      <lastaccess></lastaccess>
      <storageused></storageused>
      <transferused></transferused>
    </space>
    <space>...</space>
    <space>...</space>
  </spacedata>
</teamdrive>
```

Note: The space name field is empty by default for security reasons. You can enable the returning of space names by setting the configuration options `StoreSpaceNames` and `APIReturnSpaceNames` to `True` via the TeamDrive Hosting Service Administration Console.

4.7.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30302</primarycode>
    <secondarycode></secondarycode>
    <message>Depot-ID does not match</message>
  </exception>
</teamdrive>
```

4.8 Delete Depot

Important: This call will also delete all of the user's spaces

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>deletedepot</command>
  <requesttime></requesttime>
  <username></username>
```



```
    <depotid></depotid>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
    <apiversion>3.0.003</apiversion>
    <intresult>0</intresult>
</teamdrive>
```

4.8.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

4.9 Deactivate Depot (added in 3.0.002)

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
    <apiversion>3.0.003</apiversion>
    <command>deactivatedepot</command>
    <requesttime></requesttime>
    <username></username>
    <depotid></depotid>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
    <apiversion>1.0.004</apiversion>
    <intresult>0</intresult>
</teamdrive>
```

4.9.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

4.10 Delete a Space

Note: <spaceidlist> is a comma separated list of space-id's.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>deletespace</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <spaceidlist></spaceidlist>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.10.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

Space-ID or Combination of Space-ID and Depot-ID is Unknown

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30303</primarycode>
    <secondarycode></secondarycode>
    <message>Space-ID does not match</message>
  </exception>
</teamdrive>
```

4.11 Set Depot Limits (added in 3.0.003)

Note: The values of <disclimit> and <trafficlimit> is in Bytes: 1 KB = 1024 Bytes.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>setdepot</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <disclimit></disclimit>
  <trafficlimit></trafficlimit>
  <changeinfo></changeinfo>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.11.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

Increasing Depot Failed due to Invalid or Wrong Disclimit or Trafficlimit

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30304</primarycode>
    <secondarycode></secondarycode>
    <message>Increasing Depot failed</message>
  </exception>
</teamdrive>
```

4.12 Increase Depot Limits

Note: The value of <increaselimit> is in Bytes: 1 KB = 1024 Bytes.

Added in 3.0.003:

<increasetraffic>: value is optional; if empty, the storage limit * 10 will be used for the traffic limit

<changeinfo>: can be used as a free text field for the change history

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>increasedepot</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <increaselimit></increaselimit>
  <increasetraffic></increasetraffic>
  <changeinfo></changeinfo>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.12.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

Increasing Depot Failed due to Invalid or Wrong increaselimit

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30304</primarycode>
    <secondarycode></secondarycode>
    <message>Increasing Depot failed</message>
  </exception>
</teamdrive>
```

4.13 Decrease Depot Limits

Note: The value of <decreaselimit> is in Bytes: 1 KB = 1024 Bytes.

Added in 3.0.003:

<decreasetraffic>: value is optional; if empty, the storage limit * 10 will be used for the traffic limit

<changeinfo>: can be used as a free text field for the change history

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>decreasedepot</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <decreaselimit></decreaselimit>
  <decreasetraffic></decreasetraffic>
  <changeinfo></changeinfo>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.13.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

Decreasing Depot Failed due to Invalid or Wrong Decreaselimit

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30305</primarycode>
    <secondarycode></secondarycode>
    <message>Decreasing Depot failed</message>
  </exception>
</teamdrive>
```

4.14 Authorize Users to Create Spaces in other Depots

Note: <userlist> is a comma separated list of usernames

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>addusertodepot</command>
  <requesttime></requesttime>
  <username></username>
```

```
<depotid></depotid>
  <userlist></userlist>
</teamdrive>
```

Reply:

Note: The reply will return a base64 encoded text in the <depotdocument>-Tag.

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
  <depotdocument></depotdocument>
</teamdrive>
```

4.14.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

4.15 Remove Authorization from Users to Create Spaces in Other depots

Note: <userlist> is a comma separated list of usernames

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>deleteuserfromdepot</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <userlist></userlist>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.15.1 Error Cases

No Depot on the Server for the User

See above.

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above.

4.16 Update Contract (added in 3.0.002)

Note: <username> is optional

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>updatecontract</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
  <accountnumber></accountnumber>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.16.1 Error Cases

Depot-ID or the Combination of Username and Depot-ID is Unknown

See Above

4.17 Create and Deploy a Depot

Note: Creating a new depot and deploying the depot file to a list of users must be done by executing a few requests to different servers. It depends on whether you want to use your own Host Server or the TeamDrive Cloud Host Server.

If you are using the TeamDrive Cloud Host Servers, you have to send a *gethostfordepot* (page 19) request to the TeamDrive Registration Server. The reply will return a Hosting Service-URL dependant on your distributor code.

Send the *createdepot* (page 20)-request to the returned URL or directly to your own Host Server, if you are using one. The reply will return a depot-document. Send this document, together with a list of usernames, to the TeamDrive Registration Server using the “sendinvitation” request as described above.

4.17.1 Requesting a Hosting Service-URL

Note: In <location> send “EU”, “US”, or the IP-Address of the user. The <location> will only supported if the distributor has servers in different locations running. Otherwise the default Hosting Service will be used.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <command>gethostfordepot</command>
  <requesttime></requesttime>
  <username></username>
  <location></location>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <hosturl></hosturl>
</teamdrive>
```

4.17.2 Error Cases

User Unknown

See above

Account not Activated

See above

Invalid Location

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>1.0.004</apiversion>
  <exception>
    <primarycode>-30112</primarycode>
    <secondarycode></secondarycode>
    <message>Invalid location</message>
  </exception>
</teamdrive>
```

4.17.3 Create Depot

Note: <userlist> is a comma separated list of usernames (this parameter is optional).

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>createdepot</command>
  <requesttime></requesttime>
  <username></username>
  <storagelimit></storagelimit>
  <trafficlimit></trafficlimit>
  <userlist></userlist>
</teamdrive>
```


Reply:

Note: The reply will return a base64 encoded text in the `<depotdocument>`-Tag, which must be send as an `sendinvitation` request, with the list of users, to the Registration Server (see Registration Server API “send invitation” using the command “sendinvitation”).

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <depotdocument>...</depotdocument>
</teamdrive>
```

4.17.4 Error Cases

Creating depot failed due to invalid Depot-ID

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30302</primarycode>
    <secondarycode></secondarycode>
    <message>Depot-ID does not match</message>
  </exception>
</teamdrive>
```

Creating Depot Failed due to Invalid Storage Limit

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <exception>
    <primarycode>-30306</primarycode>
    <secondarycode></secondarycode>
    <message>Invalid storage limit</message>
  </exception>
</teamdrive>
```

4.18 Create Depot Without User (added in 3.0.002)

Note: The request is similar to *createdepot* (page 20). Might be useful if a shop application wanted to retrieve a depot before the user has an account in the shop.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>createdepotwithoutuser</command>
  <requesttime></requesttime>
  <accountnumber></accountnumber>
  <depotname></depotname>
```

```
<storagelimit></storagelimit>
<trafficlimit></trafficlimit>
</teamdrive>
```

Reply:

Note: The reply will include the depot id.

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult></intresult>
</teamdrive>
```

4.19 Assign User to Depot (added in 3.0.002)

Note: This request should be used if the depot was created using the *createdepotwithoutuser* (page 21) call. If the user does not exist yet, they will be created.

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>assignusertodepot</command>
  <requesttime></requesttime>
  <depotid></depotid>
  <username></username>
  <email></email>
  <language></language>
  <gender></gender>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <intresult>0</intresult>
</teamdrive>
```

4.19.1 Error Cases

No Depot on the Server for the User

See above

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above

4.20 Get Depot Document

Request:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <command>getdepotdocument</command>
  <requesttime></requesttime>
  <username></username>
  <depotid></depotid>
</teamdrive>
```

Reply:

```
<?xml version='1.0' encoding='UTF-8' ?>
<teamdrive>
  <apiversion>3.0.003</apiversion>
  <depotdocument>...</depotdocument>
</teamdrive>
```

4.20.1 Error Cases

No Depot on the Server for the User

See above

Depot-ID or the Combination of Username and Depot-ID is Unknown

See above

API ERROR CODES

The following table lists all API-Error-Codes that might be returned. Some of these errors might also occur when using the TeamDrive Registration Server Admin Console, as it performs Host Server API calls as well.

Registration-Server-Error-Codes:

Table 5.1: API Error Codes

Primary	Message	Comment
-30000	Access denied	
-30001	Invalid Command	
-30002	Invalid Request	
-30003	Invalid XML	
-30004	URL	
-30005	Maintenance work	This user will be handled using the webinterface of the distributor A 503 from the API-Server should be displayed as Maintenance work for the user. 503 will be mapped to -30005.
-30100	Username does not exist	
-30101	Wrong password	
-30102	Account not activated by activation mail	
-30103	Username already exists	
-30104	Email already exists	No longer used in API 1.0.003
-30105	Temporary password does not match	
-30106	Wrong activation code	
-30107	No Default Depot	
-30108	Username invalid	
-30109	Password invalid	
-30110	Email invalid	
-30111	Invitation type unknown	
-30112	Invalid location	
-30113	Temporary password expired	
-30114	Distributor of the user does not match in the database	
-30115	Invalid language	Currently not in use
-30116	Search string too short	
-30117	Activation code not found	
-30118	Account already activated	Currently not in use
-30119	Account disabled	
-30120	Account will be deleted	
-30121	Device not found	
-30122	Invalid date	
-30201	Unknown License	
-30202	License Upgrade failed	
-30203	Productname unknown	
-30204	Type unknown	

Continued on next page

Table 5.1 – continued from previous page

Primary	Message	Comment
-30205	Feature unknown	
-30206	Limit unknown	
-30207	Cancel license failed	
-30208	Downgrade license failed	
-30209	Empty list	Currently not in use
-30210	License change failed	
-30211	License in use	Currently not in use
-30301	No Depot for User	
-30302	Depot-ID does not match	
-30303	Space-ID does not match	
-30304	Increasing Depot failed	
-30305	Decreasing Depot failed	
-30306	Invalid storage limit	
-30307	Depot already exists	

APPENDIX

6.1 Abbreviations

PBAC Prime Base AutomationClient

PBAS Prime Base ApplicationServer

PBT Prime Base Talk is an object oriented language specifically designed for the programming of “server-side” functionality common to intra- and internet Web sites. A large share of the TeamDrive Host and Registration Server functionality is implemented in PBT. The code is parsed and executed by the Yvva application server components.

SAKH Server Access Key HTTP for TeamDrive 2.0 Clients

TDES Team Drive Enterprise Server

TDNS Team Drive Name Service

TDRS Team Drive Registration Server

TDSV Same as **SAKH**, but for TeamDrive 3.0 Clients: Team Drive Server

TSHS Team Drive Scalable Hosting Storage.